

N600R Wireless SSID password setting

It is suitable for : N600R, A800R, A810R, A3100R, T10, A950RG, A3000RU

Application introduction: The Wireless SSID and password are the basic information for you to connect Wi-Fi network.

But sometimes you may forget or want to change them regularly, so here we will guide you how to check or modify the wireless SSID and password.

Settings

STEP-1: Enter the setup interface

Open a browser, enter 192.168.0.1. Input User Name and password (default admin/admin) on login management interface, as follows:

Note: The default access address varies depending on the actual situation. Please find it on the bottom label of the product.



STEP-2: View or modify the wireless parameters 2-1. Check or modify in Easy Setup page.

Login management interface, first enter the Easy Setup interface, you can see wireless settings,

	D LINK Network Device	The Smartest Network Device
1600R (Firmwar	re V5.3c.2043)	A Language 🔻 🧕 🗐 Hei
	Easy Setup	
	The easy setup will guide you to configure AP for first time.	Advanced Setup
	Connect Status	
	Connect Status DHCP Mode Connected	
	Internet Setting	
	WAN Connection Type DHCP •	
	Wireless Setting Radio On/Off Enable SSID TOTOLINK_49edc4	
	Encryption WPA/WPA2-PSK Recommend Encryption Type WPA-PSK	

If you are setting up the WIFI SSID and password for the first time, you can modify the SSID in the wireless settings and recommend selecting Encryption: WPA / WPA2-PSK (default Disable) and then modify the WIFI password.



Easy Setup

The easy setup will guide you to configure AP for first time.

Advanced Setup

Connect Status

Connect Status DHCP Mode Connected

In the wireless ---Basic settings, you can set the SSID, Encryption, Password, Channel and other information

N600R (Firmware V5.3c.2043)	
-----------------------------	--

A Language 🔻 ಖ Help

System Status			
Operation Mode	Basic Setting		
Network +	-	nimum number of wireless settings fo ith only the minimum setting items.	r communication, such as SSID and Channel. The
Wireless 1 -			1
Wireless Status	Radio On/Off	Enable 🔻	
Basic Setting	SSID	TOTOLINK_N600R	
Multiple APs	Band	2.4 GHz (B+G+N+AC) V	
MAC Authentication	SSID Broadcast	Enable 🔻	
NDS Setting	Channel	Auto 🔻	
VPS Setting	Channel Bandwidth Encryption	20/40MHz V WPA/WPA2-PSK V	
Advanced Setting	Encryp Type	TKIP/AES V	3
Wireless Schedule	Key Format	ASCII V	•
QoS +	Кеу	88888888	
Firewall +			Apply
Management +			

In the wireless --- Advanced settings, you can set the Preamble Type, TX Power, Maximum of connected users and other information

N	600R (Firmware V5.3c.2043)			A Language 🔻 🧟 Help
💬 S	ystem Status			
8 0	peration Mode	Advanced Setting		
● N	etwork +		o make detailed settings for the wireless advanced setting includes iter ng page, such as Beacon Interval, Control Tx Rates and Basic Data Ra	
察 W	/ireless 1 -			
▹ Wire	eless Status	BG Protection Mode	Off 🔻	
. Ras	sic Setting	Beacon Interval	100 ms (range 20 - 999, default 100)	
	-	Data Beacon Rate(DTIM)	1 ms (range 1 - 255, default 1)	
⊩ Mul	Itiple APs	Preamble Type	Long Preamble O Short Preamble	
► MA	C Authentication	Fragment Threshold	2346 (range 256 - 2346, default 2346)	
∗ WD	S Setting	RTS Threshold	2347 (range 1 - 2347, default 2347)	
► WP	'S Setting	TX Power	● 100% ● 75% ● 50% ● 35% ● 15% 3	
		Maxnum of connected users	0 (range 0 - 32, 0 for unlimited)	
Adv	vanced Setting	AP Isolated	Disable 🔻	
 Wire 	eless Schedule	WMM Capable	Enable V	
💠 Q	o\$ +			
ê Fi	irewall +			Apply
фM	anagement +			

Questions and Answers

Q1: Can wireless signals be set to special characters?

A: Yes, WIFI SSID and WIFI passwords can be set to special characters SSID is only allowed to include Chinese and English, numbers, and special characters : ! @ # ^ & * () + _- = {} []:and space character WPA Key can contain only English, numbers and the following special character : ! @ # ^ & * () + _- = {} [] important configuration, record the password to prevent forgetting.