

How to set up static DHCP?

It is suitable for : **N150RH, N150RT, N151RT, N200RE, N210RE, N300RT, N301RT , N300RH, N302R Plus, A702R, A850R, A3002RU**

Set up steps

STEP-1: Connect your computer

Connect your computer to the router by cable or wireless, then login the router by entering http://192.168.0.1 into the address bar of your browser.



Note: The default access address varies depending on the actual situation. Please find it on the bottom label of the product.

STEP-2 :

User Name and Password are required, by default both are **admin** in lowercase letter. Click **LOGIN**.

USER LOGIN

[Forget Password?](#)

User Name

Password

STEP-3 :

Select advanced settings to enter the settings page

Model No. N100RE (Firmware V3.4.0)

- Status
- Network
- WAN Settings
- LAN Settings 1
- IPTV Settings
- DHCP&ARP Tables
- Static Route
- Routing Table
- Wireless
- QoS
- Firewall
- System

LAN Settings

Ip Address	<input type="text" value="192.168.0.1"/>
Subnet Mask	<input type="text" value="255.255.255.0"/>
DNS:	<input type="text" value="LAN-side router IP"/>
DHCP	<input type="text" value="Server"/>
DHCP Client Range	<input type="text" value="192.168.0.2"/> - <input type="text" value="192.168.0.254"/>
DHCP Lease Time	<input type="text" value="480"/> (1 ~ 10080 minutes)
Static DHCP	<input type="button" value="Set Static DHCP"/> 2
Domain Name	<input type="text" value="itotolink.net"/>
802.1d Spanning Tree:	<input type="text" value="Disabled"/>

Host Name	Ip Address	MAC Address	Time Expired(s)
DESKTOP-7QF8A9F	192.168.0.2	60:02:b4:96:37:9d	28777

STEP-4 :

Checklist the Enable Static DHCP to open the setting, input IP Address ,MAC Address and Comment. After click Apply , we can see the information in the static DHCP List.

Model No. N100RE (Firmware V3.4.0)

- Status
- Network
- WAN Settings
- LAN Settings
- IPTV Settings
- DHCP&ARP Tables
- Static Route
- Routing Table
- Wireless
- QoS
- Firewall
- System

Static DHCP Setup

Enable Static DHCP 1

2

2

2

3

IP Address	MAC Address	Comment	Select
192.168.0.10	14-da-e9-ed-ad-09	PC1	<input checked="" type="checkbox"/>